



#### Features

- 3D NAND Flash for higher durability and capacity
- SLC caching: enhances transmission speed
- Wide capacity range: 512GB to 2TB
- Advanced LDPC ECC Technology
- PCIe Gen 3 x 4 interface
- Support NVMe 1.3

## **Ordering Information**

Capacity	Part Number	EAN Code
512GB	AGI512GIMAI298	4718009611184
1TB	AGI1T0GIMAI298	4718009611191
2ТВ	AGI2T0GIMAI298	4718009611207



HIGH-PERFORMANCE

$\frown$	$\bigcirc$	
	Ð	
High Stability	Fast read and write	High Quality







## **Specifications**

- Capacity: 512GB / 1TB / 2TB
- NAND Flash: 3DNAND
- Interface: PCle Gen 3 x 4
- Form factor: M.2 2280
- MTBF: 1,600,000 hours
- Dimensions (L x W x H): 80 x 22 x 3.5mm
- Operating Voltage: 3.3V

#### Performance

- Weight: 6g
- Operating temperature: 0°C~70°C
- Storage temperature: -40°C~85°C
- Shock resistance: 1500G/0.5ms
- Certifications: CE, FCC, BSMI, VCCI, RoHS
- Warranty: 3 years

Capacity	CDM-QD		
	Seq. Read (MB/s)	Seq. Write (MB/s)	ТВЖ
512GB	2200	1300	300TB
1TB	2400	1800	600TB
2ТВ	2400	1800	1200TB

\*Performance may vary based on SSD capacity, hardware test platform, test software, operating system, and other system variables

# Schematics

50		ý = =		Ð
				<u>कवा</u> '
	.		I .	ļģ
				ø