



M.2 PCIe SSD

Features

- 3D NAND Flash for higher durability and capacity
- SLC caching: enhances transmission speed
- Wide capacity range: 1TB to 2TB
- PCIe Gen 4 x 4 interface
- Support NVMe 1.4
- NANDXtend™ ECC Technology
- Support SMART and TRIM commands

Ordering Information

Capacity	Part Number	EAN Code
1TB	AGI1T0G80AI808	4718009614499
2TB	AGI2T0G80AI808	4718009614505



SOLID-STATE DRIVE
HIGH-PERFORMANCE



High
Stability



Fast read
and write



High
Quality



M.2 SSD



Specifications

- Capacity: 1TB / 2TB
- NAND Flash: 3DNAND
- Interface: PCIe Gen 4 x 4
- Form factor: M.2 2280
- MTBF: 1,600,000 hours
- Operating Voltage: 3.3V±5%
- Humidity: 5% to~98%RH (Non-condensing)
- Operating Vibration:15G(7 to 2000Hz)
- Certifications: CE, FCC, BSMI, RoHS
- Warranty: 3 years
- Dimensions (L x W x H):
 - 80 x 22 x 5.4 mm (with heat sink)
 - 80 x 22 x 2.1 mm (without heat sink)
- Weight: 7.5g±0.2g
 - 1TB : 11.2g (w/ heat sink) / 5.2g(w/o heat sink)
 - 2TB : 11.2g (w/ heat sink) / 5.2g(w/o heat sink)
- Operating temperature: 0°C-70°C
- Storage temperature: -40°C-85°C
- Shock resistance: 1500G/0.5ms

Performance

Capacity	CDM-SEQ1M Q8T1		TBW
	Seq. Read (Up to) (MB/s)	Seq. Write (Up to) (MB/s)	
1TB	3800	2700	600TB
2TB	4000	3700	1200TB

*Performance may vary based on SSD capacity, hardware test platform, test software, operating system, and other system variables