



Features

- 3D NAND Flash for higher durability and capacity
- SLC caching: enhances transmission speed
- Wide capacity range: 1TB to 2TB
- PCle Gen 4 x 4 interface
- Support NVMe 1.4
- NANDXtend™ ECC Technology
- Support SMART and TRIM commands

Ordering Information

Capacity	Part Number	EAN Code
1TB	AGI1T0G80AI808	4718009614499
2TB	AGI2T0G80AI808	4718009614505





Specifications

Capacity: 1TB / 2TB
NAND Flash: 3D NAND
Interface: PCle Gen 4 x 4
Form factor: M.2 2280

MTBF: 1,600,000 hoursOperating Voltage: 3.3V±5%

Humidity: 5% to~98%RH (Non-condensing)
Operating Vibration:15G(7 to 2000Hz)
Certifications: CE, FCC, BSMI, RoHS

• Warranty: 3 years

• Dimensions (L x W x H):

 $80 \times 22 \times 5.4 \text{ mm}$ (with heat sink)

80 x 22 x 2.1 mm (without heat sink)

• Weight: 7.5g±0.2g

1TB: 11.2g (w/ heat sink) / 5.2g(w/o heat sink) 2TB: 11.2g (w/ heat sink) / 5.2g(w/o heat sink)

Operating temperature: 0°C-70°C
Storage temperature: -40°C-85°C
Shock resistance: 1500G/0.5ms

Performance

Capacity	CDM-SEQ1M Q8T1		
	Seq. Read (Up to) (MB/s)	Seq. Write (Up to) (MB/s)	ТВЖ
1TB	3800	2700	600TB
2ТВ	4000	3700	1200TB

^{*}Performance may vary based on SSD capacity, hardware test platform, test software, operating system, and other system variables