



Features

- 3D NAND Flash for higher durability and capacity
- SLC caching: enhances transmission speed
- Capacity up to 4TB
- PCle Gen 3 x 4 interface
- Support NVMe 1.3
- Datapath Protection
- DRAM Cache Buffer
- Support RAID Engine and Data Shaping Technology

Ordering Information

Capacity	Part Number	EAN Code
512GB	AGI512GIMAI218-CB	4718009610651
1TB	AGI1T0GIMAI218-CB	4718009610644
2TB	AGI2T0GIMAI218-CB	4718009610330
4TB	AGI4T0G38AI218-CB	4718009612167















Specifications

• Capacity: 512GB / 1TB / 2TB / 4TB

NAND Flash: 3D NAND
Interface: PCle Gen 3 x 4
Form factor: M.2 2280
MTBF: 1,600,000 hours

• Dimensions (L x W x H): 80 x 22 x 3.5mm

• Operating Voltage: 3.3V

• Weight: 6g

Operating temperature: 0°C-70°C
Storage temperature: -40°C-85°C
Shockresistance: 1500G/0.5ms

• Certifications: CE, FCC, BSMI, VCCI, RoHS

• Warranty: 3 years

Performance

Capacity	CDM-QD32		
	Seq. Read (MB/s)	Seq. Write (MB/s)	TBW
512GB	3050	2200	300TB
1TB	3450	3100	600TB
2TB	3500	3200	1200TB
4TB	3700	2950	2400TB

^{*}Performance may vary based on SSD capacity, hardware test platform, test software, operating system, and other system variables

Schematics

